

# Database Programming with SQL

6-2 Join Clauses





### Objectives

This lesson covers the following objectives:

- Construct and execute a join with the ANSI-99 USING Clause
- Construct and execute a join with the ANSI-99 ON Clause
- Construct and execute an ANSI-99 query that joins three tables

### Purpose

- As you add more commands to your database vocabulary, you will be better able to design queries that return the desired result.
- The purpose of a join is to bind data together, across tables, without repeating all of the data in every table.
- Why ask for more data than you really need?

#### **USING Clause**

- In a natural join, if the tables have columns with the same names but different data types, the join causes an error.
- To avoid this situation, the join clause can be modified with a USING clause.
- The USING clause specifies the columns that should be used for the join.

#### **USING Clause**

- The query shown is an example of the USING clause.
- The columns referenced in the USING clause should not have a qualifier (table name or alias) anywhere in the SQL statement.

SELECT first\_name, last\_name, department\_id, department\_name
FROM employees JOIN departments USING (department\_id);

FIRST_NAME	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
Jennifer	Whalen	10	Administration
Michael	Hartstein	20	Marketing
Pat	Fay	20	Marketing



#### **USING Clause**

 The USING clause allows us to use WHERE to restrict rows from one or both tables:

```
SELECT first_name, last_name, department_id, department_name
FROM employees JOIN departments USING (department_id)
WHERE last name = 'Higgins';
```

FIRST_NAME	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
Shelley	Higgins	110	Accounting

#### **ON Clause**

- What if the columns to be joined have different names, or if the join uses non-equality comparison operators such as <, >, or BETWEEN?
- We can't use USING, so instead we use an ON clause.
- This allows a greater variety of join conditions to be specified.
- The ON clause also allows us to use WHERE to restrict rows from one or both tables.

### **ON Clause Example**

• In this example, the ON clause is used to join the employees table with the jobs table.

```
SELECT last_name, job_title
FROM employees e JOIN jobs j
ON (e.job_id = j.job_id);
```

• A join ON clause is required when the common columns have different names in the two tables.

LAST_NAME	JOB_TITLE		
Gietz	Public		
Gletz	Accountant		
Higgins	Accounting		
111881113	Manager		
Whalen	Administration		
vviidicii	Assistant		
King	President		
Kochhar	Administration		
KUCIIIIai	Vice President		
De Haan	Administration		
ре паап	Vice President		
Ernst	Programmer		
Hunold	Programmer		
Lorentz	Programmer		
Hartstein	Marketing		
	Manager		

#### ON Clause with WHERE Clause

 Here is the same query with a WHERE clause to restrict the rows selected.

```
SELECT last_name, job_title
FROM employees e JOIN jobs j
  ON (e.job_id = j.job_id)
WHERE last_name LIKE 'H%';
```

LAST_NAME	JOB_TITLE
Higgins	Accounting Manager
Hunold	Programmer
Hartstein	Marketing Manager

### ON Clause with non-equality operator

- Sometimes you may need to retrieve data from a table that has no corresponding column in another table.
- Suppose we want to know the grade\_level for each employees salary.
- The job\_grades table does not have a common column with the employees table.
- Using an ON clause allows us to join the two tables

job\_grades table

GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
А	1000	2999
В	3000	5999
С	6000	9999
D	10000	14999
Е	15000	24999
F	25000	40000

### ON Clause with non-equality operator

```
SELECT last_name, salary, grade_level, lowest_sal, highest_sal FROM employees JOIN job_grades
ON(salary BETWEEN lowest_sal AND highest_sal);
```

LAST_NAME	SALARY	GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
Vargas	2500	А	1000	2999
Matos	2600	А	1000	2999
Davies	3100	В	3000	5999
Rajs	3500	В	3000	5999
Lorentz	4200	В	3000	5999
Whalen	4400	В	3000	5999
Mourgos	5800	В	3000	5999
Fay	6000	С	6000	9999



12

### Joining Three Tables

- Both USING and ON can be used to join three or more tables.
- Suppose we need a report of our employees, their department, and the city where the department is located?
- We need to join three tables: employees, departments and locations.



### Joining Three Tables Example

SELECT last\_name, department\_name AS "Department", city
FROM employees JOIN departments USING (department\_id)
JOIN locations USING (location\_id);



LAST_NAME	Department	CITY
Abel	Sales	Oxford
Davies	Shipping	South San Francisco
De Haan	Executive	Seattle
Ernst	IT	Southlake
Fay	Marketing	Toronto
Gietz	Accounting	Seattle
Hartstein	Marketing	Toronto
Higgins	Accounting	Seattle
Hunold	IT	Southlake

## Terminology

Key terms used in this lesson included:

- ON clause
- USING clause

### Summary

In this lesson, you should have learned how to:

- Construct and execute a join with the ANSI-99 USING Clause
- Construct and execute a join with the ANSI-99 ON Clause
- Construct and execute an ANSI-99 query that joins three tables

